



THREAD TRIMMER SOLENOID  
AND OIL DEPOSIT



PNEUMATICAL FOOT LIFTER, BACKTACKING  
AND 2 STITCHES LENGTH SELECTOR



THREAD TRIMMER KNIFE

MODEL	Nº s.p.m.	S.P.M.	DP x 17	8 14	301	—	—	—	ATTACHMENTS			750	MAX. mm
SW-4767H-30"	x1	2.400											
SW-4767H-30"-2	x2	2.200											
SW-4767H-30"-7	x1	2.400											
SW-4767H-30"-2-7	x2	2.200											

\* Standard gauge 8 mm. Other special gauges available: 6,4 mm, 10 mm, 12 mm and 16 mm.

1 and 2 needles compound feed sewing machine, 2.400 s.p.m. 75 cm (30") lenght arm, double dial for two separate stitch length, H.P. mechanism, thread trimmer, pneumatic bactacking and foot lifter. Stitch lenght can be selected by small front panel. Mini servo motor 1 H.P, 9 mm stitch length. Available in simple version without thread trimmer.

Máquinas de 1 y 2 agujas, triple arrastre, 2.400 p.p.m. Brazo largo de 75 cm (30") equipada con doble dial depuntada y regulador para el salto de prensatelas (mecanismo H.P). Cortahilos, atacado y alzapatas neumáticos. Incorpora 1 dial de longitud de puntada seleccionable electrónicamente mediante botonera central. Mini motor servo 1 c.v. longitud de puntada de 9 mm. Disponible en versión simple sin cortahilos.